

| | |
|--------------------------------|-----------------------------|
| Model | TD600, TD600L |
| Sizes | 3/8", 1/2", 3/4", 1" |
| Connections | NPT |
| Body Material | Stainless Steel 420F |
| Options | Insulation Cap |
| PMO Max. Operating Pressure | 600 PSIG |
| TMO Max. Operating Temperature | 800°F |
| PMA Max. Allowable Pressure | 600 PSIG up to 800°F |
| TMA Max. Allowable Temperature | 800°F @ 600 PSIG |



Typical Applications

DRIP, TRACING: TD600 model steam traps are most commonly used in drip applications, such as draining condensate from steam mains and steam supply lines. They can also be used for steam tracing applications. These traps are suitable for outdoor applications that are subject to freezing as well as superheated steam conditions. They are compact and rugged with only a single moving part. If a trap with an integral strainer is desired, the TD600S is recommended. If a fully in-line repairable design is required, the TD700S or the UTD450 with Universal Quick-Change connector is recommended.

How It Works

The disc is the only moving part inside a thermodynamic trap. When steam enters the trap, it creates an internal pressure above the disc that instantly forces the disc to close tightly on the seat, preventing the steam from escaping. The internal steam pressure (holding the disc and seat shut) eventually drops, and the trap re-opens. When condensate enters the trap, it pushes the disc upwards, allowing the condensate to freely discharge. If steam is present, the trap instantly shuts.

Features

- High pressure applications up to 600 PSIG
- Hardened stainless steel seat and disc for extended service life even at high pressure
- Single trap will operate over the entire pressure range of 3.5-600 PSIG (recommended above 30 PSIG)
- Suitable for superheated steam
- Freeze-proof when trap is piped in a vertical orientation for complete drainage of condensate
- Three-hole balanced discharge extends life of the seat area
- Trap will function in any orientation (horizontal preferred)

Sample Specification

The steam trap shall be a thermodynamic disc type with all stainless steel construction. Integral seat design and disc to be hardened for long service life. Unit shall be capable of installation in any orientation and self-draining when mounted vertically.

Installation and Maintenance

The TD600 can be installed in any orientation; however, horizontal with cap facing upward is preferred for longest service life. The one piece body-seat design is extremely simple and economical; however, this configuration is generally considered not fully repairable since the seat cannot be repaired if damaged or worn. Welding of trap body directly into pipeline is not recommended since excessive heat may cause distortion of the seat area. The TD600 does not contain an integral strainer and separate strainer should therefore be installed to protect from dirt and pipe scale. If a fully in-line repairable design or a trap that can be welded into pipeline is desired, the TD700S, TD900S or the UTD450 with Universal Quick-Change connector is recommended.

Helpful Selection Information


The TD600L has reduced size discharge orifice holes which are preferable in terms of performance, longevity, and efficiency; particularly on pressures over 150 psi. For most drip applications the 1/2" TD600L should have sufficient capacity. For higher load drip applications or if a 3/4" pipe connection is required, use 3/4" TD600L or best results. Choosing a model with a condensate handling capacity in the range of the specific application will prolong trap life.

L = Reduced Size Discharge Orifice holes which are preferable in terms of performance, longevity, and efficiency; particularly on pressures over 150 psi.

Options

An insulation cap is available to reduce cycle rates and steam loss in rain, snow, or cold environments.

ED = Etched disc for air service



| DIMENSIONS & WEIGHTS – inches | | | | | | |
|-------------------------------|-------------|------------|------|------|------|--------------|
| Size | Model Code | Connection | A | B | C | Weight (lbs) |
| 3/8" | TD600-11-N | NPT | 1.37 | 1.69 | 2.00 | 0.75 |
| 1/2" | TD600-12-N | NPT | 1.50 | 2.00 | 2.69 | 1.25 |
| 3/4" | TD600-13-N | NPT | 1.75 | 2.38 | 2.81 | 2.00 |
| 1" | TD600-14-N | NPT | 2.12 | 2.81 | 3.30 | 3.00 |
| 1/2" | TD600L-12-N | NPT | 1.50 | 1.81 | 2.71 | 1.00 |
| 3/4" | TD600L-13-N | NPT | 1.50 | 2.25 | 2.75 | 1.75 |

How to Size / Order

Select working pressure; follow column down to correct capacity (lbs/hr) block. Example:

Application: 500 lbs/hr at 100 PSIG working inlet pressure
 Size/Model: 3/4" **TD600L-13-N**

MATERIALS

| | |
|----------------|----------------------------|
| Body | Stainless Steel, AISI 420F |
| Disc | Stainless Steel, AISI 420 |
| Cover | Stainless Steel, AISI 416 |
| Insulation Cap | Stainless Steel, AISI 304 |

CAPACITIES – Condensate (lbs/hr)

| Size | Model Code | Steam Inlet Pressure (PSIG) | | | | | | | | | | | | | | | | | | | | |
|------|-------------|-----------------------------|-----|-----|-----|-----|-----|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| | | 3.5 | 5 | 10 | 15 | 20 | 25 | 30 | 40 | 50 | 75 | 100 | 150 | 200 | 250 | 300 | 350 | 400 | 450 | 500 | 550 | 600 |
| 1/2" | TD600L-12-N | 180 | 185 | 190 | 195 | 200 | 215 | 220 | 230 | 250 | 310 | 375 | 500 | 620 | 710 | 800 | 825 | 900 | 1070 | 1120 | 1185 | 1290 |
| 3/4" | TD600L-13-N | 300 | 315 | 350 | 380 | 415 | 440 | 470 | 515 | 580 | 710 | 825 | 1020 | 1165 | 1300 | 1440 | 1565 | 1670 | 1775 | 1880 | 1960 | 2060 |
| 3/8" | TD600-11-N | 180 | 185 | 190 | 195 | 200 | 215 | 220 | 230 | 250 | 310 | 375 | 500 | 620 | 710 | 800 | 825 | 900 | 1070 | 1120 | 1185 | 1290 |
| 1/2" | TD600-12-N | 300 | 315 | 350 | 380 | 415 | 440 | 470 | 515 | 580 | 710 | 825 | 1020 | 1165 | 1300 | 1440 | 1565 | 1670 | 1775 | 1880 | 1960 | 2060 |
| 3/4" | TD600-13-N | 415 | 430 | 475 | 520 | 565 | 610 | 650 | 720 | 825 | 1020 | 1185 | 1480 | 1710 | 1950 | 2110 | 2265 | 2490 | 2625 | 2780 | 2985 | 3140 |
| 1" | TD600-14-N | 650 | 680 | 740 | 815 | 885 | 940 | 1000 | 1080 | 1225 | 1500 | 1800 | 2215 | 2625 | 2935 | 3300 | 3600 | 3875 | 4120 | 4350 | 4560 | 4840 |

Notes: 1) Maximum back pressure not to exceed 80% of inlet pressure (measured in absolute pressure) or trap may not close.
 2) For optimum performance, recommended for operating pressure above 30 PSIG.