




Rev.	Description	Initiator	Date
08	ECO 14323; Increased tolerance on dowel hole positions from ±.013 to ±.025	SZJ	3/28/2016




MOUNTING SIDE



SIDE VIEW



TOOL SIDE




ISOMETRIC VIEW

Notes:

- Material: Mounting and Tool Adapter made of Aluminum, Transducer made of hardened stainless steel.
- WARNING: DO NOT LOOSEN OR REMOVE INTERFACE PLATES OR CABLE DUE TO POTENTIAL DAMAGE.**
- DO NOT EXCEED INTERFACE DEPTH. MAY CAUSE DAMAGE**
- Standard connector (not shown) has 17mm diameter & is 67.5mm long.
- Do not allow items passing through center hole to touch both the Mounting and Tool Adapter Plates or accuracy will be compromised.

NOTES: UNLESS OTHERWISE SPECIFIED.

DO NOT SCALE DRAWING. ALL DIMENSIONS ARE IN MILLIMETERS.



1031 Goodworth Drive, Apex, NC 27539, USA  
 Tel: +1.919.772.0115 Email: info@ati-ia.com  
 Fax: +1.919.772.8259 www.ati-ia.com  
 ISO 9001 Registered Company

PROPERTY OF ATI INDUSTRIAL AUTOMATION, INC. NOT TO BE REPRODUCED IN ANY MANNER EXCEPT ON ORDER OR WITH PRIOR WRITTEN AUTHORIZATION OF ATI.

DRAWN BY: J. Parker 3/14/07		TITLE	
CHECKED BY: P.Fusco 4/18/07		Mini40-E Transducer with Strain Relieved Cable	
PROJECT # -	SHEET 1 OF 1	SCALE	SIZE
		2:1	B
DRAWING NUMBER		REVISION	
9230-05-1314		08	