

Managed Ethernet Switch

L106-F2G

- ⌘ Compact Industrial Ethernet switch design
 - Flexible SFP transceiver design
 - Advanced WeOS Layer 2 functionality
 - Low power consumption
- ⌘ Designed for use in industrial applications
 - Dual 19 – 60VDC power input
 - Highly configurable I/O contact
 - Robust metal DIN rail housing
- ⌘ Robust for long service life
 - 615,000 hours MTBF to MIL-HDBK-217K
 - -40 to +70°C (-40 to +158°F) with no moving parts
 - Industrial EMC, shock and vibration testing
- ⌘ Unique future proof industrial networking solutions
 - 20 ms network ring recovery time
 - Fast reconnect for multicast protocols
 - Easy to use



EN 61000-6-1
Residential Immunity

EN 61000-6-2
Industrial Immunity

EN 61000-6-3
Residential Emission

EN 61000-6-4
Industrial Emission

EN 50121-4
Railway Trackside

The Lynx 106-F2G is a layer 2 industrial Ethernet switch, powered by the Westermo WeOS network operating system. Lynx is the most compact and has the lowest power requirements in this class of switch. Lynx 106-F2G has 4 10/100 Mbit/s ports in addition to 2 ports which can be fitted with Gbit or 100 Mbit SFP transceivers.

The Lynx is designed for simple use in industrial applications with its the robust DIN rail clip to the configurable fault contact and the industrial level dual power inputs.

Only industrial grade components are used which gives the Lynx an MTBF of 615,000 hours and ensures a long service life. A wide operating temperature range -40 to +70°C (-40 to +158°F) can be achieved with no moving parts or cooling holes in the case. Lynx has been tested both by Westermo and external test houses to meet many EMC, isolation, vibration and shock standards, all to the highest levels suitable for heavy industrial environments and rail trackside application.



WeOS has been developed by Westermo to allow us to offer cross platform and future proof solutions. WeOS can deliver 20 ms ring recovery performance even for networks with video or EtherNet/IP traffic. For more WeOS functionality please see the WeOS datasheet.

Ordering Information

Art.no	Description
3643-0230	L106-F2G, Managed Ethernet Switch
1211-2027	CLI Cable (Console) (Accessories)
3125-0001	PS-30, Power supply, DIN mounted (Accessories)

Specifications L106-F2G

Dimensional drawing



Dimension W x H x D 52 x 100 x 101 mm (2.04 x 3.93 x 3.97 in)
 Weight 0.7 kg
 Degree of protection IP40

Power	
Operating voltage	19 to 60 VDC
Rated current	180 mA (330 mA) @ 24 VDC (with 500 mA USB load) 90 mA (170 mA) @ 48 VDC (with 500 mA USB load)

Interfaces	
Ethernet TX	4 x RJ-45, 10 Mbit/s, 100 Mbit/s,
Ethernet SFP pluggable connections (FX or TX)	SFP (LC connector), 100 Mbit/s or 1000 Mbit/s transceivers supported
Digital I/O	1 x 4-position detachable screw terminal
USB	1 x USB 2.0 host interface
Console	1 x 2.5 mm jack, use only Westermo cable 1211-2027

Temperature	
Operating	-40 to +70°C (-40 to +158°F)
Storage & Transport	-50 to +85°C (-58 to +185°F)

Agency approvals and standards compliance	
EMC	EN 61000-6-1, Immunity residential environments
	EN 61000-6-2, Immunity industrial environments
	EN 61000-6-3, Emission residential environments
	EN 61000-6-4, Emission industrial environments
	EN 50121-4, Railway signalling and telecommunications apparatus
	IEC 62236-4, Railway signalling and telecommunications apparatus
Safety	UL/IEC/EN 60950-1, IT equipment
Marine	DNV GL rules for classification – Ships and offshore units